



Nebula

Part of the Primalume lighting program.



Type (diameter)	50mm series	111mm series
Art. number	133020	133021
Size	Size l x w x h (mm): 70 x 50 x 60	Size l x w x h (mm): 111 x 111 x 105
Fixture	Compatible with all major wall and ceiling fixture brands	Compatible with all major wall and ceiling fixture brands
Efficiency	140lm/Watt	140lm/Watt
Consumption	1,35 < W < 7,7	1,35 < W < 7,7
Color temp.	Tunable: between 2200K and 6500K	Tunable: between 2200K and 6500K
Luminous flux (neutral light)	1060lm @ 4000K	1060lm @ 4000K
Luminous flux (warm light)	480lm @ 2200K	480lm @ 2200K
Luminous flux (cold light)	580lm @ 6500K	580lm @ 6500K
Lightsource	LED SMD	LED SMD
Beam Angle of LED	135 Degrees	135 Degrees
Beam Angle reflector	Any available reflector beam angle can be provided	Any available reflector beam angle can be provided
CRI	> 90 Ra	> 90 Ra
Certification	CE, RoHS etc.	CE, RoHS etc.
Dimmable	Yes, linear or scenes	Yes, linear or scenes
Warranty:	10 years (SWOP*)	10 years (SWOP*)





PRIMALUME
LOW VOLTAGE IMPACT

Nebula

Part of the Primalume lighting program.



* During the warranty period we swap the defect product. The defect product will either be repaired, or a refurbished product will be sent back to the customer for reuse. If it is not possible to do this a new product will be sent. As our products are designed in modular way, they can easily be taken apart and repaired or refurbished. In this way we make sure that we maximize the lifespan of the product and postpone the moment it needs to be recycled. For more details on our warranty and swap policy, please read our general terms and conditions.

